


TVR S3 Brake Pipe Specifications

Ridged Pipes

Pipe No	Description	End 1		Length (metres)	End 2	
		Type	Thread		Type	Thread
1	Servo to Rear Bias Regulator	Male	M10 x 1.00	0.65	Male	M10 x 1.00
2	Servo Front Off Side	Male	M10 x 1.00	0.95	Female	M10 x 1.00
3	Servo Front Near Side	Male	M10 x 1.00	1.48	Female	M10 x 1.00
4	Front Off Side Flex to Flex	Female	M10 x 1.00	0.2	Female	M10 x 1.00
5	Front Near Side Flex to Flex	Female	M10 x 1.00	0.2	Female	M10 x 1.00
6	Rear Bias Regulator to Rear 'T'	Male	M10 x 1.00	2.4	Male	M10 x 1.00
7	Rear 'T' to Rear Flex Off Side	Male	M10 x 1.00	0.65	Female	M10 x 1.00
8	Rear 'T' to Rear Flex Near Side	Male	M10 x 1.00	0.24	Female	M10 x 1.00
9	Rear Flex to Calliper Off Side	Male	M10 x 1.00	0.5	Male	M10 x 1.00
10	Rear Flex to Calliper Near Side	Male	M10 x 1.00	0.5	Male	M10 x 1.00

NB. All male ends as follows:



Flexible Pipes

Pipe No	Description	End 1		Length (metres)	End 2	
		Type	Thread		Type	Thread
1	Front Short Off Side	Male	M10 x 1.00	0.22	Male Bulkhead with lock Nut	M10 x 1.00
2	Front Short Near Side	Male	M10 x 1.00	0.22	Male Bulkhead with lock Nut	M10 x 1.00
3	Front Long Off Side	Male Bulkhead with lock Nut	M10 x 1.00	0.4	Male Bulkhead with lock Nut	M10 x 1.00
4	Front Long Near Side	Male Bulkhead with lock Nut	M10 x 1.00	0.4	Male Bulkhead with lock Nut	M10 x 1.00
5	Rear Off Side	Male Bulkhead with lock Nut	M10 x 1.00	0.25	Male Bulkhead with lock Nut	M10 x 1.00
6	Rear Near Side	Male Bulkhead with lock Nut	M10 x 1.00	0.25	Male Bulkhead with lock Nut	M10 x 1.00

NB. All Flexible Bulkhead Ends as follows:

